

Baler Wrappers

Rime Agri Silage Baler and Packing Machines are combining round baler and wrapping in single processes. It is an enormously profitable and saving time process. Rime Agri Silage Baler and Packing Machine compress the chopped materials in the best way by forming the bale and wrapping the material with the stretch film to make airproof baler to create the best environment for product fermentations. Moreover, It is increasing the quality of the livestock feed.



Baler Wrappers

MODEL NAME	SB 1150 (1 TONNE)	SB 1150 PRO (1 Tonne,Ground loading)	SB 850
ENERGY			
ENERGY SOURCE	3 Phease (380V)	3 Phase (380 V)	Electricity (380 V)
TOTAL POWER REQUIREMENT (kW)	30	35	24
POWER CONSUMPTION (kWh/TON)	2,58	3	2,05
MIN POWER GENERATOR (kW)	30	36	24
BALE CAVITY ENGINE POWER (kW)	18,5	18,5	15
CAPACITY			
BALE CAPACITY (BALE/HOUR)	50 Bale	50 Adet	45-55 Bale
DAILY CAPACITY (BALE/DAY)	500 Bale	500 Adet	500 Bale
BUNKER CAPACITY	7,5 m2	5,5 m2	4 m2
BUNKER TYPE	Top loading	Ground loading	
CONTROL SYSTEM			PLC
ELECTRONIC CONTROL SYSTEM	PLC	PLC	Standart
TOUNCH SCREEN	Standart	Standart	
BALE DIMANSIONS			900 mm
HEIGHT	1,200 mm	1,200 mm	850 mm
DIAMETER	1,150 mm	1,150 mm	400-600 kg
WEIGHT	850-1200 kg	850-1200 kg	
WRAP AND NET FILM DIMENSIONS			
WRAP DIMANSIONS	500 mm and 750 mm	500 mm and 750 mm	500 mm
NET FILM DIMANSIONS	1,230 mm and 1,250mm	1,230 mm and 1,250mm	900 mm and 1050 mm; strech can be used with same dimensions
OTOMATIC LUBRICATION	Standart	Standart	Standart
PRESSING UNIT	Endless belt	Endless belt	Endless belt
GENERAL			
LENGHT (CARRIAGE)	750 cm	817 cm	670 cm
LENGHT (WORKING)	1,068 cm	1,018 cm	935 cm
WIDHT (CARRIAGE)	250 cm	250 cm	230 cm
WIDHT (WORKING)	260 cm	327 cm	240 cm
HEIGHT (CARRIAGE)	395 cm	363 cm	340 cm
HEIGHT (WORKING)	360 cm	352 cm	310 cm
AXLE	Single	Single	Single
TRACTOR LINK	1 Point towbar	1 Point towbar	1 Point towbar
WEIGHT	9160 kg	9160 kg	6860 kg